

Each set of basketball goals is made up of two goals, manufactured according to European standards EN-1270 CLASS C TYPE 7 in terms of safety, stability and resistance, composed of:

Description

Anti Vandall proof basketball goals manufactured in steel tube of 114 x 3 mm (4 ") in steel quality S 275 JOH, S 235 JR, (DD 11) SAE 1008, both the central tube and the projection, main mast structure model ORIGINAL B2 In its lower part, the ground anchor incorporates metal cone reinforcement system, giving greater strength and stability to the frame.

Fastenings made of 300 x 300 x 10 mm steel plate, from which four 650 mm long corrugated rods emerge in the form of inverted J, this will be at level 0 flush with the planimetry of the pavement, leaving only four threads of 20 mm on which the basket will be fixed with self-locking nuts, and anti-injury plastic caps.

Metallic 1500x1050x4mm backboard structure is attached directly to the main mast in its lower part by 425x180x10mm plate plate system and 950x200mm cold laminated U plate that joins the lower part of the frame with the upper part, also incorporates two upper tie-downs as braces in 35x2mm tube from the top of the 50x30x2mm metal frame from the board to the main mast. The projection of the board on the ground flies 1.65 m.

The price includes two units of basketball goals. For one unit, contact us. OPTIONS:

34043A SET OF FRONTAL CILINDIRIC PROTECTIONS CUSHION

Set of protections of basketball, mast protection made with foam and flame retardant fabric laminated fireproof B1 / M2.

Technical characteristics

- Metallic backboard in hot dip galvanized steel 1500 x 1050 x 4 mm.
- Tilting basketball reinforced rings. (34065)
- Nylon nets in 4.5mm. (34068)
- Main structure Hot dip galvanized 450°C













